

VICTAULIC COUPLINGS

High Pressure Couplings

IAC

INDUSTRIAL ACCESSORIES COMPANY



Style 77 Flexible Coupling

For use with grooved end pipe

Cross-ribbed construction design for higher working pressure. Provides flexibility for expansion, contraction, and deflection.

Pipe Sizes from 3/4" to 24"



Style 75 Flexible Coupling

For use with grooved end pipe

Flexible coupling for use where moderate pressures are expected and weight considerations are a factor.

Pipe Sizes from 1" to 12"



Style 78 Snap-Joint Coupling

For use with grooved end pipe

Designed for quick disconnect service. Mated housings are hinged with an attached locking handle for assembly.

Pipe Sizes from 1 1/4" to 8"



Style 99 Plain End Roust-A-Bout Coupling - No pipe groove required

Specially designed for **plain end** steel and stainless steel pipe. Gripping teeth provide a strong component for joining plain and beveled end (including Schedule 80 steel pipe). Not to be used on plastic pipe, pipe with brittle linings, cast or ductile iron pipe nor any pipe with a surface hardness greater than 150 Brinell.

Pipe Sizes from 1" to 18"

IAC also supplies a complete line of grooved end pipe fittings.

- Elbows
- Laterals
- Adaptors
- Reducers
- Tees
- Caps
- Wyes
- Plugs

IAC Product Lines Also Include:

- Tubing
- Hose
- Knife Gate Valves
- Butterfly Valves
- Blowers
- Pipe
- Fans
- Motors
- Service & Installation

FOR MORE INFORMATION OR TO PLACE AN ORDER CONTACT IAC TODAY

PB102011

4800 Lamar Avenue / Mission, KS 66202 / USA 800.334.7431

www.iac-intl.com